

## Amendments to the Specification

*Please replace paragraph 22 with the following amended paragraph:*

In practice, the pattern forming for the end panels 12 and 14 and side panels 16, 18, as well as mid panel 20 (i.e. layers 21, 23) is depicted in Fig. 6 wherein seam line 24 is indicated by edges 24A, 25A, 25B and 24B associated respectively with panel parts 14A, 22B and 14B. Side panel 18 is then sewn to panel sections 12A, 14A along seam line edges 12C/18C and ~~14B~~14C/18B. The mid panel 20 may be a separate panel piece or integral with sides 12 and 14 as depicted in Figure 6.

*Please replace paragraph 24 with the following amended paragraph:*

The mid-panel 20 may be connectable to the bottom panel 10 and the end panels 12 and 14 respectably by releasable fasteners (e.g., 90, 92 92 in Figure 4) and more particularly by a loop type fastener such as known by the trade name Velcro. In this manner, the mid-panel 20 may be disengaged to from the bottom wall panel 10, and the first and third end walls 12 and 14 to provide access to a connected set of compartments 40 and 42 defining a single compartment. Thus, the separate compartments 40 and 42 will be joined together to form a single compartment. Alternatively, the mid-panel 20 could be sewn in place as described previously to provide first and second separate compartments 40 and 42 for the bag.

[01]